# F1930A

Din rail industrial computer with Intel E3845 CPU, 4x GbE RJ45, 2x Rs232, 5x RS485 COM, 9~36V DC input



### **Specifications**

Motherboard		
CPU	Onboard Intel quad-core E3845 1.91GHz processor with 2MB L2 cache	
BIOS	SPI FLASH BIOS	
System memory	Max 8GB RAM	
	Storage	
Interface	One mSATA Interface	
Hard Drive	MAX 512G mSATA SSD	
CF slot	None	
Ethernet		
LAN Port RJ45	Four 10/100/1000Mbps RJ45 network interfaces	
BYPASS	One channel LAN BYPASS	
Indicator	LAN link, active, speed LED, built in BYPASS status LED	
ξ	System I/O	
USB	Two USB2.0	
COM RS232	Two RS232(Rj45 interface)	
COM RS485	Five RS485 Phoenix Interfaces	
Indicator	One Power LED, one HDD LED	
Display	One VGA interface, supports hot plug, maximum resolution support 2048x1536	
Reset	One built-in reset button	
DIO	8 digital level input and output interfaces (4 inputs, 4 outputs)	
Watchdog	1~255 seconds programmable software watchdog	

software watchdog

#### **Features**


- Din rail industrial computer, Aluminum extrusion case fanless design
- Onboard Intel Atom quad-core E3845 processor, 1.91GHz, 2MB cache
- One 204pin 1600MHz DDR3L RAM, max 8GB RAM
- · Four Gigabit Ethernet ports, support one channel LAN BYPASS
- Two RS232 RJ-45 port
- · Five RS-485 COM isolated interface
- Optional a 4G model(external SIM slot)
- Four USB2.0, mSATA storage
- Two 9~36V DC inputs, with alarm for power failure
- Support DIN RAIL type installation for industrial application


4G module	One full Netcom 4G module, external SIM slot	
Power Supply		
Power consumption	60W power adapter	
Power input	Dual 9 ~ 36V wide range DC input	
Environments		
Mounting	Support DIN-RAIL rail type installation	
Operate Temperature	-40°C ~ 70°C	
Storage Temperature	-50°C ~ 85°C	
Operate Humidity	5% ~ 85% non-condensing @ 40°C	
Storage Humidity	5% ~ 95% non-condensing	
Mechanical		
Chassis Color	Silver	
Front panel	Front panel silk-screen [Customized LOGO optional]	
Construction	Aluminum extrusion chassis	
Dimensions (W x H x D)	60.8 x 158.1 x 122 mm	
Weight	3 ka	

## **Ordering information**

Model	Descriptions
F1930A	Din rail Industrial embedded computer, Aluminum extrusion chassis, E3845 CPU, 4 x GbE RJ45 with one lan bypass, 2x Rs232 and 5x RS485 COM, Dual 9 ~ 36V input, 60W Power adapter

#### Pictures & Views





## **Dimensions Diagram**

