

IDM-057

Small size 5.7" LCD industrial touch panel monitor



Features

- 5.7"VGA TFT LCD Panel support 640 × 480 pixels, 700 cd/m2 High brightness for sun-readable
- 6mm Aluminum front bezel panel and with resistive touch screen
- Rugged construction and modularized design
- VGA Input signal
- OSD control keys to optimize the display
- AC 100-240V wide range external ac adapter with Lockable connector
- DC 8 ~ 30V input power module(Optional)
- Panel (Flush) mount with bracket
- NEMA4 / IP 65 compliant front panel
- With standard VESA hole (75x75 mm), support desk top stand /wall mount/ swing arm mounting

Specifications

LCD Panel	
Display Type	5.7" VGA TFT LCD(Backlight LED)
Resolution	640 × 480
Max.color	262K
Luminance	700 cd/m2
View Angle	160°(H) , 140°(V)
Pixel Pitch	0.180 x 0.180 mm
Contrast Ratio	800 : 1
Response Time	25 ms
LED MTBF	50,000hrs
System	
Touch screen	Resistive touch screen
Input Signals	VGA
DC input	DC 2Pin aviation Connector

Power Supply	Input100~240VAC,50/60Hz; Output: 12V/3A ,36Watts external AC Adapter
Mechanical and Environmental	
Operating Temperature	0 °C to 60 °C
Storage Humidity	5% to 95%@ 40°C , on-condensing
Vibration	5-17Hz/1mm amplitude, 17-640Hz/1.5g acceleration
Shock	10G peak acceleration (11 msec. duration)
Dimensions (WxHxD)	186 x 145 x 40 mm
Weight	Net: 2.5kg , Gross:4kg

Ordering Informations

IDM-057	High brightness Industrial monitor with 5.7" TFT LCD, 5.7" touch screen, VGA
---------	--

Dimensions Diagram

