

IDM-17V

17" LCD industrial panel monitor with HDMI VGA



Features

- 17" SXGA TFT LCD Panel support 1280 x 1024 pixels, 350 cd/m2 brightness
- 6mm Aluminum bezel panel with touch screen/strengthen glass
- Rugged construction and modularized design
- VGA + HDMI + Audio Input signal
- 2 x stereo speakers for industrial automation system voice output
- OSD control keys to optimize the display
- AC 100-240V wide range external ac adapter
- NEMA4 / IP 65 compliant front panel
- Panel (Flush) mount with bracket or standard VESA hole (100x100mm) supports desktop stand / wall mount/ swing arm mount

Specifications

LCD Panel	
Display Type	17" SXGA TFT LCD
Resolution	1280x1024
Max.color	16.7M
Luminance	350 cd/m2
View Angle	170°(H) , 160°(V)
Pixel Pitch	0.264 x 0.264mm
Contrast Ratio	1000:1
Response Time	5 ms
LCD MTBF	50,000hrs
System	
Touch screen(optional)	Resistive touch screen(RS232/USB)
Input Signals	VGA, HDMI, Audio
Power Supply	100~240VAC,50/60Hz, DC12V@ 5A / 60W ,external ac adapter

DC Power (optional)	DC 9~ 36v input power module
Mechanical and Environmental	
Construction	Heavy duty steel and aluminum front panel
Operate temperature	0 °C to 50 °C
Storage temperature	-20 °C to 60 °C
Storage humidity	10% to 90% non-condensing
Anti-Vibration	17HZ-500 HZ 1G PTP
Anti-Shock	1G / peak(11m sec)
Dimensions (WxHxD)	408 x 345 x 47 mm
Weight	Net: 5.0kg , Gross:7.5 kg

Ordering Informations

IDM-17V	17" LCD Industrial Panel Monitor with VGA , HDMI , Audio input
---------	--

Dimensions Diagram

